

<b>DESEMPEÑO PERFORMANCE</b>	Velocidad de flujo de Aire ( a 1 m de distancia)	Air Flow Velocity (1 m )	3= 5.1 m/s 2= 4.35 m/s 1= 3.4 m/s
	RPM		3= 1576 2= 1415 1= 1160
	Oscilacion	Oscillation	95°
	Inclinacion	Tilt	No
<b>CT RIC O ELE CT</b>	Amp (Velocidad Alta) A	Amperage (High Speed)	0,66 A
<b>CARACTERISTICAS FEATURES</b>	Potencia (Velocidad Alta) W	Watts (High Speed)	85 W
	Dimension del Producto ensamblado	Unit Dimension	Altura: 132 cm Base : 50 cm
	Controles: Electronico/Digital, Boton de Presion (mecanico) or Interruptor Giratorio (Mecanico)	Controls: Electronic/Digital, Mechanical Push Button or Mechanical Rotary Switch	Interruptor giratorio  Mechanical Rotary Switch
	Control Remoto (alambrico , inalambrico)	Remote Control (Basic, Full-Featured, etc.)	No
	Numero de velocidades	Number of speeds	3
	Fusible protector termico	Thermic Fuse	SI
	Para montar en pared	Wall Mount	No
	Cable ( tipo y especificaciones)	Cord (type & rating)	SPT-2 60°C VW-1 18 AWG X 2 C
	Longitud del cable	Cord Length	8'
	Aspa: # de hojas y material	blade	3 hojas (metalicas) 3 blades (metalic)
	Otras características:	Other features:	Protectores de aspa metalicos
<b>CERTIFICACION</b>	Certiificacion NOM-003-SCFI-200	NOM approved	NOM-424-ANCE
	UL certificacion	UL approved	NO
<b>EMBARQUES SHIPPING</b>	Dimension de empaque del producto	Carton Dimension	675 mm x 145 mm x 500 mm
	Volumen	ft <sup>3</sup>	1.969 ft <sup>3</sup>
	Peso Neto (Kg/lbs)	Net Weight (Kg/lbs)	4,67 kg
	Peso Bruto (Kg/lbs)	Gross Weight (Kg/lbs)	5,6 kg
	Cantidad aprox. contenedor	HC Quantity (aprox)	48' HC : 1597 pcs 53' HC : 1776 pcs
	Garantia	Warranty	Un Año